


DESCRIPTION

The RSS Ultra Slim LED Strip fixture features an architectural design, providing a sleek lighting solution for various settings. Tailored for commercial, industrial, institutional, and retail spaces, this luminaire series is specifically crafted to illuminate storage/utility areas, coves, display cases, shops, task areas, and general spaces.



Client:	
Order #:	
Project:	
Type:	

FEATURES

- Field selectable 3500k (warm/neutral white), 4000k (neutral white), and 5000k (cool white) color temperatures.
- Long-life LEDs provide 196,000 hours of operation with at least 70% of initial lumen output (L70), and 60,000 hours with at least 90% of initial lumen output (L90).
- LED chromaticity based on < 4-step ANSI quadrangles.
- LED color maintenance < 0.002 chromaticity shift ($\Delta u'v'$) over the initial 6,000 hours of operation.
- RSS/4 provides a range of 3,500 to 5,000 nominal lumens. RSS/8 provides a range of 7,000 to 10,000 nominal lumens.
- Easy installation in new construction or retrofit.
- Universal 120-277 AC voltage (50-60Hz) is standard.
- 0-10vdc dimming drivers are standard.
- Power factor > 0.90.
- Total harmonic distortion < 20%.
- Color rendering index > 80.
- Steel housing and PMMA lens.
- Optional emergency drivers and occupancy sensors are available.

PERFORMANCE DATA

CRI

80+

CCT

3500K, 4000K, 5000K

Projected Lifetime

>196,000 Hours (L70)
>60,000 Hours (L90)

Dimming

0-10V Dimming Standard,
10% down to 100%

Operating Temperature

-20°C to +50°C Ambient

Warranty

5 year Standard
10 year Optional

ORDERING INFORMATION

RSS							
------------	--	--	--	--	--	--	--



	B	C	D	E	F	G	H	
A	FIXTURE SERIES		D		G		H	
	RSS	Ultra Slim LED Strip	CCT		OPTIONS			
			35	3500K	EM		Emergency	
B	LENGTH		40	4000K	M		Motion Sensor	
	4	c	50	5000K	H		WARRANTY²	
	8	8'	E		-		5 Year Warranty	
C	WATTAGE/LUMENS (4')		VOLTAGE		10		10 Year Warranty	
	25	25W/3590 ¹	UNV		10L		10 Year Warranty including labor	
	30	30W/4258 ¹	120-277V					
	35	35W/4804 ¹	F					
	WATTAGE/LUMENS (8')		FINISH					
	50	50W/7207 ¹	WH					
	60	60W/8440 ¹	White					
	70	70W/9483 ¹						

¹ Delivered Lumens (5000K)



² 5 Year Warranty is Standard unless specified

DIMENSIONS

RSS/4:



RSS/8:



PHOTOMETRIC DATA

RSS
Luminaire Data

Description	4' Strip Light Slim
Total Lumens	4,804
Input Wattage	34
Efficacy (lm/W)	140
Spacing Criterion (0-180°)	1.24
Spacing Criterion (90-270°)	1.34

Zonal Lumen Summary

Zone	Lumens	%Fixt
0-20°	492	10.2%
0-30°	1,049	21.8%
0-40°	1,725	35.9%
20-50°	1,948	40.5%
40-70°	1,949	40.6%
0-60°	3,111	64.8%
0-80°	4,095	85.2%
0-90°	4,372	91.0%
90-180°	432	9.0%
0-180°	4,804	100.0%

