



Client:	
Order #:	
Project:	
Type:	



**DESCRIPTION**

Introducing the RFLP, a high-performance LED panel designed with a unique back-lit system for extended durability and superior lighting solutions. The RFLP features switchable CCT and switchable wattage, allowing users to effortlessly select their desired settings using fixture-mounted switches. This innovative fixture offers five different wattage options, ranging from 17W to 50W—delivering an impressive 145 lumens per watt, making it the only product on the market with such versatility while eliminating the need to stock multiple configurations. Whether you need low wattage or high wattage, the RFLP is designed to meet all your lighting needs in one convenient fixture.

**FEATURES**

- Selectable Wattage and CCT gives five light output and three CCT options reducing SKUs and making project ordering and logistics easier.
- Order a single model and use the selections to match your project application's requirements.
- Light weight construction is 40% lighter than edge light designs on average.
- Reduced weight allows contractors to speed up installation and move on to their next project.
- No gaps in the construction eliminates light leak.
- Fits standard 1" and 9/16" T-Bar grid ceilings found in most offices.

**CONSTRUCTION & ELECTRICAL**

- Die formed and stamped steel housing.
- RoHS Compliant with minimal Mercury.
- Weight: 2x4: 19.5lbs, 2x2: 10lbs, 1x4: 10.25lbs
- Low Flicker with Standard 0-10V Dimming
- Standard 120-277VAC Input Voltage
- Power Factor ≥ 0.9
- THD ≤ 10%

**PERFORMANCE DATA**

**EFFICACY**

143 - 160 Lumens per Watt (LPW)

**CCT/CRI**

3500K, 4000K or 5000K, 80+ CRI

**RATED LIFE**

>150,000 Hours (L70)  
>50,000 Hours (L90)

**LUMEN OUTPUT**

Lumen Output Ranges from 2,686 to 7,650 Lumens

**OPERATING TEMPS**

-20°C to 50°C (- 4°F - 122°F) Ambient

**WARRANTY**

5 year Standard  
10 Year Extended  
10 Year Extended with Labor

**ORDERING INFORMATION**

RFLP / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_  
 SERIES      SIZE      WATTAGE      CCT      VOLTAGE      DRIVER FEATURES      FINISH      CONTROLS      EMERG. BATT.      WARRANTY

FIXTURE SERIES	
RFLP	Revo LED Flat Panel
SIZE	
14	1x4 Nominal Size
22	2x2 Nominal Size
24	2x4 Nominal Size
WATTAGE*	
40WS	17W, 20W, 25W, 32W, 40W Select. (2,660 - 5,750 lm) (1x4, 2x2)
50WS	17W, 25W, 30W, 35W, 50W Select. (2,700 - 7,250 lm) (2x4)

\*Delivered Lumens based on 4000K

CCT	
CS	80+ CRI, 35K, 40K, 50K CCT Select.
VOLTAGE	
UNV	Universal 120-277VAC
DRIVER FEATURES	
10V	0-10V Dimming
12A	12V Aux Power & 0-10V Dimming
FINISH	
WH	White Finish

CONTROLS	
SRB	Sensor Ready Plug'n'Play Bracket
MDLP	Motion PIR Occ. & Daylight Harv., Plug'n'Play
MDLPBA	Motion PIR Occ. & Daylight Harv., Plug'n'Play, Bluetooth App
EMERGENCY BATT. BACKUP	
EM8	8 Watt (900 lm) 90 Min. Emerg. Batt.
WARRANTY	
-	5 Year Warranty (Standard)
10Y	10 Year Warranty
10YL	10 Year Warranty with Labor

<sup>1</sup> 5 Year Warranty is Standard unless specified



**PHOTOMETRIC DATA**

MODEL NUMBER	INPUT WATTAGES	LUMEN OUTPUTS*	EFFICACY
RFLP/22/40WS	17W / 20W / 25W / 32W / 40W	2,670 / 3,100 / 3,800 / 4,725 / 5,750	143 - 158 LPW
RFLP/24/50WS	17W / 25W / 30W / 35W / 50W	2,720 / 3,900 / 4,600 / 5,290 / 7,260	153 - 160 LPW

\*Lumen Outputs based on 4000K/5000K

**DIMENSIONS**

