



Client:	
Order #:	
Project:	
Type:	



PERFORMANCE DATA

EFFICACY

≥ 130 Lumens per Watt (LPW)

CCT/CRI

3500K, 4000K or 5000K, 80+ CRI

RATED LIFE

>100,000 Hours (L70) >50,000 Hours (L90)

LUMEN OUTPUT

Lumen Output Ranges from 2,686 to 7,650 Lumens

OPERATING TEMPS

-20°C to 50°C (- 4°F - 122°F) Ambient

WARRANTY

5 year Standard 10 Year Extended 10 Year Extended with Labor

FEATURES

- · Door frame kit allows for quick and easy installation.
- An architectural styled V lens provides diffuse light while increasing visual comfort.
- Selectable Wattage and CCT gives four light output and three CCT options reducing SKUs and making project ordering and logistics easier.
- Order a single model and use the selections to match your project application's requirements.
- Light weight construction is 40% lighter than edge light designs on average.
- · Reduced weight allows contractors to speed up installation and move on to their next project.
- No gaps in the construction eliminates light leak.
- Fits standard 1" and 9/16" T-Bar grid ceilings found in most offices.

ORDERING INFORMATION

VORTEX-KIT	/	/	/	/	/	/	/	/	/
SERIES	SIZE	WATTAGE	CCT	VOLTAGE	DRIVER	FINISH	CONTROLS	EMERG.	WARRANT
					FEATURES			BATT	

FIXTURE SERIES		
VORTEX- KIT	V Lens LED Center Basket Troffer Kit	
SIZE		
14	1x4 Nominal Size	
22	2x2 Nominal Size	
24	2x4 Nominal Size	
WATTAGE		
39WS	19W, 24W, 32W, 39W Select. (2,470 - 5,070 lm) (1x4, 2x2)	
49WS	29W, 34W, 39W, 49W Select. (2,700 - 7,250 lm) (2x4)	

001					
CS	80+ CRI, 35K, 40K, 50K CCT Select.				
VOLTAGE					
UNV	Universal 120-277VAC				
DRIVER FEATURES					
10V	0-10V Dimming				
12A	12V Aux Power & 0-10V Dimming				
FINISH					
WH	White Finish				
CU	Custom Finish (Contact Factory)				

CONSTRUCTION & ELECTRICAL

· Die formed and stamped steel housing.

• RoHS Compliant with minimal Mercury.

Standard 120-277VAC Input Voltage

• Power Factor ≥ 0.9

• THD ≤ 10%

• Low Flicker with Standard 0-10V Dimming

CONTROLS

SRB	Sensor Ready Plug'n'Play Bracket (Standard)	
MDLP	Motion PIR Occ. & Daylight Harv., Plug'n'Play	
MDLPBA	Motion PIR Occ. & Daylight Harv., Plug'n'Play, Bluetooth App	
EMERGENCY BATT. BACKUP		
EM8	8 Watt (900 lm) 90 Min. Emerg. Batt.	
EM15	15 Watt (1500 lm) 90 Min. Emerg. Batt.	
WARRANTY		
-	5 Year Warranty (Standard)	
10Y	10 Year Warranty	
10YL	10 Year Warranty with Labor	





CLOSE UP DETAIL VIEW





